

ENVIRONMENTAL CONTROL DUCTING

Engineered Performance™

Ducting offers a complete line of flexible ducting products to meet your industrial heating requirements.

Drawing on four decades of experience and fully integrated manufacturing capabilities, we are well positioned to meet your quality and service requirements.

ENGINEERED
PERFORMANCE™
DUCTING

Distributed by:



AN ISO 9001:2000 REGISTERED
COMPANY

Portable Heater Ducting

Canvas Heater Sock



Application:

In cold weather conditions, deliver indirect-fired preheated air from ground heating equipment to various temporary and permanent shelters.

Temperature Handling:

Range: -60°F to 300°F
(-51°C to 149°C)

Standard Diameters:

12-inch & 16-inch
(305mm & 406mm)

Standard Length:

12 foot & 15 foot
(3.7 m & 4.6 m)

Features:

- Canvas socks provide a low-cost solution for heat delivery.
- Canvas fabric is treated for mildew, rot, water and flame resistance.
- A heavy-duty fiberglass liner provides added protection from burnout near heater unit. Socks are available with partially and fully lined fiberglass options.
- Only fire resistant materials are used.
- The duct is wire reinforced to prevent collapsing and to support bending.
- Two tie straps with clip buckles help to compress the duct for storage and transport.

Coupling System:

- Our standard canvas sock uses a black pin-lock coupling (two-pin spring attachment). Sharp edges are removed for safe handling.
- Optional end finishes are available.



Pin-lock Coupling

PRODUCT BULLETIN – 660 series

©2008 ENGINEERED PERFORMANCE™ DUCTING, ALL RIGHTS RESERVED