

# ENVIRONMENTAL CONTROL DUCTING

Engineered Performance™

Ducting offers a complete line of flexible ducting products to meet your industrial heating requirements.

Drawing on four decades of experience and fully integrated manufacturing capabilities, we are well positioned to meet your quality and service requirements.

ENGINEERED  
PERFORMANCE™  
DUCTING

Distributed by:



AN ISO 9001:2000 REGISTERED  
COMPANY

## Portable Heater Ducting HT-W Heater Duct



### Application:

In extreme weather conditions, deliver indirect-fired preheated air from ground heating equipment (hot-boxes) to various temporary and permanent shelters.

### Standard Diameters:

6-inch, 12-inch, 16-inch & 20-inch  
(152mm, 305mm, 406mm & 508mm)

### Temperature Handling:


Range: -65°F to 500°F  
(-53°C to 260°C)

### Features:

- Special silicone coated fiberglass fabric.
- Continuous service temperature range -65°F to 500°F (-53°C to 260°C).
- Remains very flexible in cold weather conditions.
- Wearstrip attached to provide abrasion resistance.
- Only fire resistant materials are used.
- Fabric material is flame resistant in accordance with the Canadian Standards Association Standard CAN/CSA-M427-M91 'Fire-Performance and Antistatic Requirements for Ventilation Materials.'
- The duct is reinforced using an internal coiled spiral wire.

### Coupling System:

- Our standard end finish consists of our wire round/rope end rings covered in two plies of fabric.
- Other end finishes are available on request



AIRFLOW →

PRODUCT BULLETIN – 620 series

©2008 ENGINEERED PERFORMANCE™ DUCTING, ALL RIGHTS RESERVED